

UNT E-MV UN 66

TRANSMISSION

Description

Automatic Transmission Fluid formulated with selected fully synthetic base stocks and latest additive technology available that provides excellent service in applications calling for low and ultra low viscosity ATF, such as: Toyota Type WS, Nissan Matic S and Hyundai SP-IV.

With the use of fully synthetic base stocks and stability of this finished oil, these helps in protecting against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -45° C. Moreover, it improves overall transmission durability and cleanliness.

Properties

- τ Provides excellent oxidation and thermal stability for longer life.
- τ Superior wear protection to protect critical transmission components.
- τ Application in low viscosity & ultra low viscosity auto transmission.
- τ Excellent rust and corrosion protection.

Technical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.845
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.72
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.66
Viscosity Index	ASTM D 2270	-	160
Appearance	Visual	-	Red

Specifications

τ AISIN	JWS 3309 ATF, ATF-0T4
τ AISIN	JWS 3324 ATF, ATF-0WS
τ ALLISON	C2
τ ALLISON	C3
τ ALLISON	C4
τ ATF	134
τ ATF	3100 PL085
τ ATF	3353
τ ATF	3403-M115
τ ATF	DX-VI
τ ATF	ETL-7045 E
τ ATF	K17
τ ATF	L12108
τ ATF	LA 2634
τ ATF	M-1375.4
τ ATF	M-1375.6
τ ATF	N402
τ ATF	SP-III
τ BENTLEY	P/N PY112995PA
τ BMW	ATF 3+
τ BMW	ATF 4
τ BMW	ATF 6
τ BMW	ETL-7045
τ BMW	ETL-7045 E
τ BMW	ETL-8072B
τ BMW	LA 2634
τ BMW	LT 71141
τ BMW	M-L12108
τ BMW	P/N 81 22 9 400 272
τ BMW	P/N 81 22 9 400 275
τ BMW	P/N 81 22 9 407 858
τ BMW	P/N 81 22 9 407 859
τ BMW	P/N 83 22 0 024 249
τ BMW	P/N 83 22 0 024 359
τ BMW	P/N 83 22 0 026 922
τ BMW	P/N 83 22 0 142 516
τ BMW	P/N 83 22 0 397 114
τ BMW	P/N 83 22 0 402 413
τ BMW	P/N 83 22 0 403 248
τ BMW	P/N 83 22 0 403 249
τ BMW	P/N 83 22 2 152 426
τ BMW	P/N 83 22 2 163 514

“Your Reliable Lubrication Choice”



Specifications

τ BMW	P/N 83 22 2 220 438
τ BMW	P/N 83 22 2 220 440
τ BMW	P/N 83 22 2 220 442
τ BMW	P/N 83 22 2 289 720
τ BMW	P/N 83 22 2 305 396
τ BMW	P/N 83 22 2 305 397
τ BMW	P/N 83 22 2 355 599
τ BMW	P/N 83 22 2 355 601
τ BMW	P/N 83 22 7 542 290
τ BMW	P/N 83 22 9 407 765
τ BMW	P/N 83 22 9 407 807
τ BOSCH	BOSCH TE-ML 09
τ CITROEN	Z 000169756
τ DAIHATSU	D3-SP
τ FCA	8 & 9 SPEED ATF, P/N 68218925AA/AB
τ FCA	ASRC
τ FCA	ATF+
τ FCA	ATF+2
τ FCA	ATF+3
τ FCA	ATF+4
τ FCA	AW-1, P/N 68092912AA
τ FCA	DEX-VI, P/N 68043742AA
τ FCA	FIAT 9.55550-AV1
τ FCA	FIAT 9.55550-AV2
τ FCA	FIAT 9.55550-AV4
τ FCA	FIAT 9.55550-AV5
τ FCA	FIAT 9.55550-AV6
τ FCA	MB 236.10/12, P/N 05127382AA
τ FCA	P/N 05127382
τ FCA	P/N 68157995AA/AB
τ FCA	P/N 68333587AA
τ FCA	SP-4, P/N 68171866AA
τ FCA	SP-III
τ FCA	SP-IV, P/N 68171866AA
τ FCA	SP-IV, P/N 68171869AA
τ FCA	TYPE 7176E
τ FCA	TYPE 9602
τ FORD	ESP-M2C138-CJ
τ FORD	ESP-M2C166-H
τ FORD	P/N XT-10-QLV [LV]
τ FORD	P/N XT-2-QDX [M]
τ FORD	P/N XT-2-QSM [SYN]

“Your Reliable Lubrication Choice”



Specifications

τ FORD	P/N XT-5-QM [V]
τ FORD	P/N XT-5-QSM [V SYN]
τ FORD	P/N XT-6-QSP [SP]
τ FORD	P/N XT-8-QAW [PREMIUM]
τ FORD	P/N XT-9-QMM5 [FRN5]
τ FORD	WSS-M2C922-A1
τ GM	ATF Z1, SATURN P/N 22717466
τ GM	AW1, P/N 19256039
τ GM	DEX [6032M]
τ GM	DEX HP [GMW 16974]
τ GM	DEX-B [6032M]
τ GM	DEX-IIC [6137M]
τ GM	DEX-IID [GM 6137M]
τ GM	DEX-IIE [GM 6137M]
τ GM	DEX-IIIF [GM 6297M]
τ GM	DEX-IIIG [GM 6417M]
τ GM	DEX-IIIH [GM N10055]
τ GM	P/N 19 40 700
τ GM	P/N 19 40 767
τ GM	P/N 21005966
τ GM	P/N 88900925
τ GM	P/N 9985010
τ GM	P/N 9986195
τ GM	SATURN T-IV Fluid SATURN P/N 22689186
τ GM	TYPE A SUFFIX A
τ GM	WS, P/N 88863400
τ GM	WS, P/N 88863401
τ HONDA / ACURA	ATF DW-1 P/N 08200-9008)
τ HONDA / ACURA	ATF Type 3.0 P/N 08200-9016-A
τ HONDA / ACURA	ATF Type 3.1 P/N 08200-9017
τ HONDA / ACURA	ATF Z1, P/N 08200-9001
τ HONDA / ACURA	ATF Z1, P/N 08200-9001A
τ HYUNDAI / KIA	ATF RED-1K
τ HYUNDAI / KIA	ATF SP-IV
τ HYUNDAI / KIA	GENUINE ATF
τ HYUNDAI / KIA	JWS 3314
τ HYUNDAI / KIA	P/N 00232-19023
τ HYUNDAI / KIA	P/N 040000C90SG
τ HYUNDAI / KIA	P/N 04500-00140
τ HYUNDAI / KIA	P/N UM040 CH20 Red-1
τ HYUNDAI / KIA	SP
τ HYUNDAI / KIA	SP4-M1

“Your Reliable Lubrication Choice”



Specifications

τ HYUNDAI / KIA	SPH-IV
τ HYUNDAI / KIA	SP-II
τ HYUNDAI / KIA	SP-III
τ HYUNDAI / KIA	SP-IV
τ HYUNDAI / KIA	SP-IV-RR
τ HYUNDAI / KIA	WS, SPEC NWS-9638
τ ISUZU	ATF II
τ ISUZU	ATF III
τ ISUZU	ATF WSI
τ ISUZU	GENUINE ATF
τ ISUZU	P/N 08200-9001
τ ISUZU	SCS
τ JAGUAR	02JDE 26444
τ JAGUAR	FLUID 8432
τ JAGUAR	JLM 20238
τ JAGUAR	JLM 20292
τ JAGUAR	JLM 21044
τ JAGUAR	K17, JATCO 3100 PL085
τ JAGUAR	LT 71141
τ JAGUAR	WSS-M2C922-A1
τ JAMA	JASO M315, Class 1-A
τ JAMA	JASO M315, Class 1-A-LV
τ LAND ROVER	ATF N402
τ LAND ROVER	AW-1 P/N LR0022460: LV
τ LAND ROVER	JWS 3309US
τ LAND ROVER	P/N TYK500050
τ LAND ROVER	LR 023288
τ LAND ROVER	LR 023289
τ LAND ROVER	P/N TYK500050
τ MAN	339A
τ MAN	339D
τ MAN	339F
τ MASERATI	OIL NO. 231603
τ MAZDA	ATF FZ
τ MAZDA	ATF M-5 P/N 0000-23-ATF -M5
τ MAZDA	ATF N-1
τ MAZDA	ATF S-1
τ MAZDA	F-1
τ MAZDA	JWS3317
τ MAZDA	M3
τ MAZDA	TYPE T-IV, JWS 3309 ATF
τ MERCEDES	A 0019892203

“Your Reliable Lubrication Choice”



Specifications

τ MERCEDES	ATF 3403-M115
τ MERCEDES	MB 236.1
τ MERCEDES	MB 236.10
τ MERCEDES	MB 236.11
τ MERCEDES	MB 236.12
τ MERCEDES	MB 236.14
τ MERCEDES	MB 236.15
τ MERCEDES	MB 236.2
τ MERCEDES	MB 236.41
τ MERCEDES	MB 236.5
τ MINI	ATF JWS 3309, P/N 83 22 0 402 413
τ MITSUBISHI	ATF-J2
τ MITSUBISHI	ATF-J3
τ MITSUBISHI	DIA QUEEN ATF-MA1, P/N MZ320775
τ MITSUBISHI	DIA QUEEN ATF-PA, P/N 4030401
τ MITSUBISHI	DIA QUEEN AW
τ MITSUBISHI	DII
τ MITSUBISHI	DIII
τ MITSUBISHI	SP, P/N MS991156
τ MITSUBISHI	SP-II
τ MITSUBISHI	SP-III
τ MITSUBISHI	SP-IV
τ NISSAN	FLUID A
τ NISSAN	MATIC D
τ NISSAN	MATIC J, P/N 999MP-MTJ00P
τ NISSAN	MATIC K
τ NISSAN	MATIC R, P/N 999MP-MTR00P
τ NISSAN	MATIC S, P/N 999MP-MTS00P
τ NISSAN	MATIC W
τ NISSAN	N402
τ PEUGEOT	P/N Z 000169756
τ PORSCHE	JWS 3309,P/N 000 043 205 28
τ PORSCHE	LT 71141
τ PORSCHE	P/N 000 043 204 41
τ PORSCHE	P/N 000 043 204 63
τ PORSCHE	P/N 000 043 304 00
τ PORSCHE	P/N 000 043 304 01
τ PORSCHE	P/N 000 043 305 42
τ PORSCHE	P/N 000 043 305 43
τ PORSCHE	P/N 000 043 305 54
τ PORSCHE	P/N 000 043 306 24
τ PORSCHE	P/N 958 300 540 00

“Your Reliable Lubrication Choice”



Specifications

τ PORSCHE	P/N 958 300 901 00
τ PORSCHE	P/N 999 917 547 00 (A2)
τ PORSCHE	P/N 000 043 205 09
τ PSA	AL4 / 4HP20, P/N 9730AE
τ PSA	B71 2340
τ RENAULT	DP-0
τ RENAULT	MATIC D2
τ RENAULT	SATF-D
τ ROLLS ROYCE	OIL NO. PL 31493PA
τ SAAB	ATF HP
τ SAAB	JWS 3309
τ SAAB	P/N 93 160 393
τ SAAB	P/N 93 165 147
τ SATURN	DEX-IIIG
τ SATURN	T-IV FLUID , P/N 22689186
τ SSANGYONG	DSIH 5M-52
τ SSANGYONG	DSIH 5M-66
τ SUBARU	ATF HP P/N K0140Y0700
τ SUBARU	ATF HP P/N SOA635040
τ SUBARU	ATF-WS
τ SUZUKI	ATF 2326
τ SUZUKI	ATF 2384K
τ SUZUKI	ATF 3314
τ SUZUKI	ATF 3317
τ SUZUKI	ATF 5D06
τ SUZUKI	MATIC D
τ SUZUKI	MATIC J
τ SUZUKI	MATIC S
τ TOYOTA	ATF FZ
τ TOYOTA	JWS 3309, Type T-IV, P/N 08886-81015
τ TOYOTA	JWS 3324, ATF WS (or NWS9638)
τ TOYOTA	TYPE D-II
τ TOYOTA	TYPE T
τ TOYOTA	TYPE T-II
τ TOYOTA	TYPE T-III
τ VOLVO	P/N 1161521
τ VOLVO	P/N 1161621
τ VOLVO	P/N 1161640
τ VOLVO	P/N 1161540
τ VOLVO	P/N 31 256 774, 31 256 775
τ VOLKSWAGEN / AUDI	G 052 162 (-A1, -A2) [AG4]
τ VOLKSWAGEN / AUDI	G 052 533

“Your Reliable Lubrication Choice”



Specifications

τ	VOLKSWAGEN / AUDI	G 052 990 A2
τ	VOLKSWAGEN / AUDI	G 055 005 A2
τ	VOLKSWAGEN / AUDI	G 055 025 (-A2)
τ	VOLKSWAGEN / AUDI	G 055 162 A2 or A6
τ	VOLKSWAGEN / AUDI	G 055 540 A2
τ	VOLKSWAGEN / AUDI	G 060 162 A2
τ	VOLKSWAGEN / AUDI	G US 000 162
τ	VOLKSWAGEN / AUDI	LT 71141
τ	ZF	LIFEGUARDFLUID 5 (ZF No. S671 090 170)
τ	ZF	LIFEGUARDFLUID 6 (ZF No. S671 090 255)
τ	ZF	LIFEGUARDFLUID 8 (ZF No. S671 090 312)
τ	ZF	LIFEGUARDFLUID 9 (ZF No. AA01.500.001)
τ	ZF	TE-ML 11A
τ	ZF	TE-ML 11B

18/10/2024
5392G3ATFREVE3