

UNT E-MV UN 88

TRANSMISSION

Description

Fully synthetic automatic transmission fluid formulated with selected high viscosity index synthetic base stocks and latest additive technology that provides excellent service in a wide variety of North American, European, and Asian vehicles.

This product is recommended for use in all GM vehicles DII, DIII(G), DIII(H). It exceeds the published JASO 1A or Allison C-4 fluid specifications and meets the requirements of Toyota Type T-IV level of anti-shudder durability (ASD).

Properties

- τ Provides excellent oxidation and thermal stability for longer life
- τ Superior wear protection to protect critical transmission components
- τ Excellent viscosity stability (high VI), application in a wide variety of Auto Transmissions
- τ Enhanced fluidity at very low temperature service

Technical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.853
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	35.38
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	6.86
Viscosity Index	ASTM D 2270	-	157
Appearance	Visual	-	Red

“Your Reliable Lubrication Choice”



Specifications

τ AISIN	JWS 3309 ATF, ATF-0T4
τ ALLISON	389
τ ALLISON	C2
τ ALLISON	C3
τ ALLISON	C4
τ ATF	3100 PL085
τ ATF	3403-M115
τ ATF	ETL-7045 E
τ ATF	K17
τ ATF	LA 2634
τ ATF	N402
τ ATF	SP-III
τ BMW	ATF4
τ BMW	ETL-7045
τ BMW	ETL-7045 E
τ BMW	ETL-8072B
τ BMW	LA 2634
τ BMW	LT 71141
τ BMW	P/N 81 22 9 400 272
τ BMW	P/N 81 22 9 400 275
τ BMW	P/N 81 22 9 407 858
τ BMW	P/N 81 22 9 407 859
τ BMW	P/N 83 22 0 024 249
τ BMW	P/N 83 22 0 024 359
τ BMW	P/N 83 22 0 026 922
τ BMW	P/N 83 22 0 402 413
τ BMW	P/N 83 22 0 403 248
τ BMW	P/N 83 22 0 403 249
τ BMW	P/N 83 22 2 220 438
τ BMW	P/N 83 22 2 220 440
τ BMW	P/N 83 22 2 220 442
τ BMW	P/N 83 22 7 542 290
τ BMW	P/N 83 22 9 407 765
τ BMW	P/N 83 22 9 407 807
τ BOSCH	BOSCH TE-ML 09
τ CITROEN	Z 000169756
τ DAIHATSU	D3-SP
τ FCA	ASRC
τ FCA	ATF+
τ FCA	ATF+2
τ FCA	ATF+3
τ FCA	ATF+4

“Your Reliable Lubrication Choice”



Specifications

τ FCA	FIAT 9.55550-AV1
τ FCA	FIAT 9.55550-AV4
τ FCA	MB 236.10, P/N 05127382AA
τ FCA	MB 236.12, P/N 05127382AA
τ FCA	P/N 68333587AA
τ FCA	SP-III
τ FCA	TYPE 7176E
τ FCA	TYPE 9602
τ FORD	ESP-M2C138-CJ
τ FORD	ESP-M2C166-H
τ FORD	P/N XT-2-QDX [M]
τ FORD	P/N XT-2-QSM [SYN]
τ FORD	P/N XT-5-QM [V]
τ FORD	P/N XT-5-QSM [V SYN]
τ FORD	P/N XT-8-QAW [PREMIUM]
τ FORD	P/N XT-9- QMM5 [FNR5]
τ FORD	SPEC WSS-M2C922-A1
τ GM	ATF Z1, SATURN P/N 22717466
τ GM	DEX [GM 6032M]
τ GM	DEX-B [GM 6032M]
τ GM	DEX-IIC [6137M]
τ GM	DEX-IID [GM 6137M]
τ GM	DEX-IIE [GM 6137M]
τ GM	DEX-IIIF [GM 6297M]
τ GM	DEX-IIIG [GM 6417M]
τ GM	DEX-IIIH [GM N10055]
τ GM	P/N 19 40 700
τ GM	P/N 19 40 767
τ GM	P/N 21005966
τ GM	P/N 88900925
τ GM	P/N 9985010
τ GM	P/N 9986195
τ GM	SATURN T-IV FLUID, SATURN P/N 22689186
τ GM	TYPE A SUFFIX A
τ HONDA/ACURA	ATF Z1, P/N 08200-9001
τ HONDA/ACURA	ATF Z1, P/N 08200-9001A
τ HYUNDAI/KIA	ATF RED-1K
τ HYUNDAI/KIA	GENUINE ATF
τ HYUNDAI/KIA	JWS 3314
τ HYUNDAI/KIA	P/N 00232-19023
τ HYUNDAI/KIA	P/N 04500-00140
τ HYUNDAI/KIA	P/N UM040 CH20 RED-1

“Your Reliable Lubrication Choice”



Specifications

τ HYUNDAI/KIA	SP
τ HYUNDAI/KIA	SP-II
τ HYUNDAI/KIA	SP-III
τ ISUZU	ATF II
τ ISUZU	ATF III
τ ISUZU	GENUINE ATF
τ ISUZU	P/N 08200-9001
τ JAGUAR	JLM 20238
τ JAGUAR	JLM 20292
τ JAGUAR	JLM 21044
τ JAGUAR	K17, JATCO 3100 PL085
τ JAGUAR	LT 71141
τ JAGUAR	WSS-M2C922-A1
τ JAMA	JASO M315, CLASS 1-A
τ LAND ROVER	ATF N402
τ LAND ROVER	JWS3309US
τ MAN	339A
τ MAN	339D
τ MAN	339F
τ MAZDA	ATF M-5 P/N 0000-23-ATF -M5
τ MAZDA	ATF N-1
τ MAZDA	ATF S-1
τ MAZDA	F-1
τ MAZDA	JWS3317
τ MAZDA	M3
τ MAZDA	TYPE T-IV, JWS 3309 ATF
τ MERCEDES	A 0019892203
τ MERCEDES	ATF 3403-M115
τ MERCEDES	SHEET 236.1
τ MERCEDES	SHEET 236.10
τ MERCEDES	SHEET 236.11
τ MERCEDES	SHEET 236.2
τ MERCEDES	SHEET 236.5
τ MERCEDES	SHEET 236.8
τ MINI	ATF JWS 3309, P/N 83 22 0 402 413
τ MITSUBISHI	ATF-J2
τ MITSUBISHI	DIA QUEEN AW
τ MITSUBISHI	DII
τ MITSUBISHI	DIII
τ MITSUBISHI	SP, P/N MS991156
τ MITSUBISHI	SP-II
τ MITSUBISHI	SP-III

“Your Reliable Lubrication Choice”



Specifications

τ NISSAN	FLUID A
τ NISSAN	MATIC D
τ NISSAN	MATIC J, P/N 999MP-MTJ00P
τ NISSAN	MATIC K
τ NISSAN	N402
τ PEUGEOT	P/N Z 000169756
τ PORSCHE	JWS 3309, P/N 000 043 205 28
τ PORSCHE	LT 71141
τ PORSCHE	P/N 000 043 204 41
τ PORSCHE	P/N 000 043 204 63
τ PORSCHE	P/N 000 043 305 42
τ PORSCHE	P/N 958 300 901 00
τ PORSCHE	P/N 999 917 547 00 (A2) or P/N 000 043 205 09
τ PSA	AL4, P/N 9730AE
τ PSA	4HP20, P/N 9730AE
τ PSA	B71 2340
τ RENAULT	DP-0
τ RENAULT	MATIC D2
τ RENAULT	SATF-D
τ ROLLS ROYCE	OIL NO. PL 31493PA
τ SAAB	ATF HP
τ SAAB	JWS 3309
τ SAAB	P/N 93 160 393
τ SATURN	DEX-IIIG
τ SATURN	T-IV FLUID, P/N 22689186
τ SSANGYONG	DSIH 5M-52
τ SSANGYONG	DSIH 5M-66
τ SUBARU	ATF HP, P/N K0140Y0700, P/N SOA635040
τ SUZUKI	ATF 2326
τ SUZUKI	ATF 2384K
τ SUZUKI	ATF 3314
τ SUZUKI	ATF 3317
τ SUZUKI	ATF 5D06
τ SUZUKI	MATIC D
τ SUZUKI	MATIC J
τ TOYOTA	JWS 3309, TYPE T-IV, P/N 08886-81015
τ TOYOTA	TYPE D-II
τ TOYOTA	TYPE T
τ TOYOTA	TYPE T-II
τ TOYOTA	TYPE T-III
τ VOLVO	P/N 1161521
τ VOLVO	P/N 1161621

“Your Reliable Lubrication Choice”



Specifications

τ VOLVO	P/N 1161640; P/N 1161540
τ VOLVO CE	97340, AT100
τ VOLVO CE	97341, AT101
τ VW/AUDI	G 052 162 (-A1, -A2) [AG4]
τ VW/AUDI	G 052 990 A2
τ VW/AUDI	G 055 025 (-A2)
τ VW/AUDI	G US 000 162
τ VW/AUDI	LT 71141
τ ZF	LIFEGUARDFLUID 5 (ZF No. S671 090 170)
τ ZF	TE-ML 05L
τ ZF	TE-ML 11A
τ ZF	TE-ML 11B
τ ZF	TE-ML 21L

18/10/2024
5392G3ATFREV1