

“Your Reliable Lubrication Choice”



UNT E-ATF 10HP

TRANSMISSION

Description

Fully Synthetic Automatic Transmission Fluid tailored with selected premium quality synthetic base stocks and superior additive technology that provides outstanding service in applications requiring ultra low viscosity specifications such as Mazda ATF 7 and Nissan Matic P.

This product offers enhanced oxidation stability and overall transmission durability, protecting against thermal breakdown at high operating temperatures while providing great performance at low temperatures.

Properties

- τ Superior wear protection to protect critical transmission components
- τ Outstanding rust and corrosion protection
- τ Provides excellent oxidation control and thermal stability for longer life
- τ Much enhanced fluidity at low temperature service

Technical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.841
Flash Point	ASTM D 92	°C	190
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	17.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	4.1
Viscosity Index	ASTM D 2270	-	133
Appearance	-	-	Amber

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warrants only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.

“Your Reliable Lubrication Choice”



Suggested for the Following Uses

τ AISIN	AW-2
τ ATF	D971
τ BMW	ATF 7
τ BMW	P/N 83 22 2 413 477
τ BYD	DHT
τ FORD	P/N XT-12-ULV [ULV]
τ GM	DEX ULV, P/N 19352619
τ MAZDA	ATF A7
τ MERCEDES	SHEET 236.15
τ MERCEDES	SHEET 236.16
τ MERCEDES	SHEET 236.17
τ NISSAN	MATIC P, P/N 999MP-MTP10P
τ NORTH AMERICAN OEM	MULTIPLE OEMs
τ PSA	16 350 560 80
τ TOYOTA	TE
τ VOLVO	P/N 31 492 172
τ VOLVO	P/N 31 492 173

31 August 2026

7923-3-ULVREVO

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warrants only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.