

## UNT E-CVT LV

### TRANSMISSION

#### Description

---

**Continuously Variable Transmission Fluid blended from high-performance fully synthetic base oils and carefully selected additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents.**

This oil is an automatic transmission well-balanced fluid specially designed for use in latest generations of Continuously Variable Transmissions (CVT) which transfer traction via steel-made traction chains or belts. It provides outstanding power transmission ratios and better fuel-economy performance of CVTs as compared with the regular automatic transmissions, many car makers have been adopting CVTs in more and more models.

#### Properties

---

- τ Excellent low temperature fluidity, reducing start up wear
- τ Provides excellent friction, oxidation and thermal stability
- τ Outstanding anti-wear properties and oil film thickness
- τ Compatible with a wide range of seals

#### Technical Characteristics

---

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.8385
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.18
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	6.201
Viscosity Index	ASTM D 2270	-	201
Appearance	Visual	-	Amber

*"Your Reliable Lubrication Choice"*



## Specifications

---

τ AUDI/ VW	P/N G 052 180 (-A2)
τ AUDI/ VW	P/N G 052 516 A2
τ BMW/ MINI/ PUNCH	EZL 799
τ BMW/ MINI/ PUNCH	EZL 799A
τ BMW	P/N 83 22 0 136 376
τ BMW	P/N 83 22 0 429 154
τ CHERY	CVTF WCF-1
τ CHRYSLER / FCA	MOPAR CVTF+4 P/N 05191184A
τ DAIHATSU	AMMIX CVTF- DFE
τ DAIHATSU	AMMIX CVTF- DTC
τ DODGE/ JEEP	NS-2
τ FCA	CVTF+4 P/N 05191184AA
τ FORD	CFT23
τ FORD	CFT30
τ FORD	MERC C
τ FORD	WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
τ GM	CVTF I-GREEN2
τ GM	CVT P/N 19260800
τ GM	DEX-CVT
τ GM	HP-CVT P/N19355873
τ HONDA	CVTF P/N 08200-9006
τ HONDA	HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
τ HONDA	HCF-2 P/N 08200-HCF2
τ HYUNDAI / KIA	SP-CVT 1
τ IDEMITSU	CVTF-EX1
τ MAZDA	CVTF 3320
τ MINI COOPER	ZF CVT V1
τ MITSUBISHI	DIAMOND GREEN CVTF-J1
τ MITSUBISHI	DIAMOND GREEN CVTF-J4
τ NISSAN	NS-1
τ NISSAN	NS-2
τ NISSAN	NS-3
τ PROTON	PUNCH CVT; CVTF EX-1 (SFU)
τ RENAULT	ELFMATIC
τ SATURN	P/N 22688912
τ SHELL	GREEN 1V
τ SUBARU	LINEARTRONIC CVTF
τ SUBARU	LINEARTRONIC CVTF-II; P/N K0425Y0711
τ SUBARU	LINEARTRONIC CV-30 P/N K0425Y0710
τ SUBARU	e-CVTF
τ SUBARU	i-CVTF
τ SUBARU	HIGH TORQUE P/N K0421Y0700

*“Your Reliable Lubrication Choice”*



## Specifications

---

τ SUZUKI	CVT FLUID GREEN 1
τ SUZUKI	CVT FLUID GREEN 2
τ SUZUKI	CVTF 3320
τ SUZUKI	NS-2
τ TOYOTA / LEXUS	FE
τ TOYOTA / LEXUS	TC

5/19/2025  
5800G3LONS3REV3

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warrants only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.