

UNT URACING DIAMOND

MCO - JASO MA2

Description

UNT URACING DIAMOND is a PAO-fortified 4T motorcycle oil formulated with the latest lubrication technology aimed to provide optimal protection for modern engines. Enhanced with a robust additive package, it surpasses stringent requirements for emissions control and oil consumption

UNT URACING DIAMOND enhances fuel efficiency, providing consumers with fuel cost savings. By ensuring proper lubrication, it minimizes internal engine friction, allowing for improved engine responsiveness and ensuring smooth, efficient operation.

Properties

- ┆ Avoid harmful effects of lubricant contamination
- ┆ Good control of wear and sludge formation
- ┆ Forms a strong emulsion to protect the oil pumping system
- ┆ Super fluidity over a wide range of temperatures and operating conditions

Technical Characteristics

Test Description	Method	Unit	5W40	5W50
SAE Viscosity Grade	SAE J 300	-	5W40	5W50
Density @ 15 °C	ASTM D 4052	kg/L	0.851	0.850
Flash Point	ASTM D 92	°C	218	220
Pour Point	ASTM D 97	°C	-42	-39
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	79.4	119.6
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.7	18.5
Viscosity Index	ASTM D 2270	-	195	174
TBN	ASTM D 2896	mgKOH/g	6.8	6.8
Appearance	-	-	Purple	Blue

Suggested for the following uses

- ┆ API SP
- ┆ JASO MA2

16 October 2025
7231-34-MA2REV0