

“Your Reliable Lubrication Choice”



油耐特 E-ATF 10HP

变速箱油

商品说明

全合成自动变速箱油采用精选优质合成基础油和卓越的添加剂技术，可在需要超低粘度规格的应用中提供出色的服务，例如马自达 ATF 7 和日产 Matic P。

该产品具有增强的氧化稳定性和整体传动耐久性，可在高温工作条件下防止热击穿，同时在低温下提供优异的性能。

特点

- τ 有卓越的磨损保护作用，能保护关键的传动部件
- τ 杰出的防锈和防腐蚀保护
- τ 提供出色的氧化控制和热稳定性，以延长使用寿命
- τ 增强低温运作时的流动性

技术特性

测试内容	测定方式	单位	
比重 @ 15 °C	ASTM D 4052	kg/L	0.841
闪点（开口杯）	ASTM D 92	°C	190
倾点	ASTM D 97	°C	-45
运动粘度 @ 40°C	ASTM D 445	cSt	17.9
运动粘度 @ 100°C	ASTM D 445	cSt	4.1
粘度指数	ASTM D 2270	-	133
颜色	-	-	琥珀色

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511
Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warrants only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.

“Your Reliable Lubrication Choice”



产品规格

τ AISIN	AW-2
τ ATF	D971
τ BMW	ATF 7
τ BMW	P/N 83 22 2 413 477
τ BYD	DHT
τ FORD	P/N XT-12-ULV [ULV]
τ GM	DEX ULV, P/N 19352619
τ MAZDA	ATF A7
τ MERCEDES	SHEET 236.15
τ MERCEDES	SHEET 236.16
τ MERCEDES	SHEET 236.17
τ NISSAN	MATIC P, P/N 999MP-MTP10P
τ NORTH AMERICAN OEM	MULTIPLE OEMs
τ PSA	16 350 560 80
τ TOYOTA	TE
τ VOLVO	P/N 31 492 172
τ VOLVO	P/N 31 492 173

31 August 2026
7923-3-ULVREV

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warrants only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.