

## 油耐特 E-CVT LV

變速箱油

### 商品說明

無段變速箱油由高性能全合成基礎油和精心挑選的添加劑混合而成，包括摩擦改進劑、清潔分散劑、氧化抑制劑、粘度指數改進劑、腐蝕抑制劑和消泡劑。

該油是專為最新一代無段變速箱(CVT)設計的自動變速箱均衡油，該變速箱透過鋼製牽引鍊或皮帶傳輸牽引力。與普通自動變速箱相比，它提供了出色的動力傳輸比和更好的燃油經濟性，許多汽車製造商已在越來越多的車型中採用CVT。

### 特點

- τ 優異的低溫流動性，減少啟動磨損
- τ 提供優異的摩擦、氧化和熱穩定性
- τ 提供優異的穩定動力
- τ 適用於各種密封圈

### 技術特性

測試內容	測定方式	單位	
比重 @ 15 °C	ASTM D 4052	kg/L	0.839
閃點 (開口杯)	ASTM D 92	°C	198
傾點	ASTM D 97	°C	-45
運動黏度 @ 40°C	ASTM D 445	cSt	26.2
運動黏度 @ 100°C	ASTM D 445	cSt	6.2
黏度指數	ASTM D 2270	-	201
外觀	Visual	-	綠色

## 规格

---

τ 奧迪/大眾	P/N G 052 180 (-A2)
τ 奧迪/大眾	P/N G 052 516 A2
τ 寶馬/迷你/PUNCH	EZL 799
τ 寶馬/迷你/PUNCH	EZL 799A
τ 寶馬	P/N 83 22 0 136 376
τ 寶馬	P/N 83 22 0 429 154
τ 奇瑞	CVTF WCF-1
τ 克萊斯勒/FCA	MOPAR CVTF+4 P/N 05191184A
τ DAIHATSU	AMMIX CVTF- DFE
τ DAIHATSU	AMMIX CVTF- DTC
τ 道奇/吉普	NS-2
τ FCA	CVTF+4 P/N 05191184AA
τ 福特	CFT23
τ 福特	CFT30
τ 福特	MERC C
τ 福特	WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
τ 通用汽車	CVTF I-GREEN2
τ 通用汽車	CVT P/N 19260800
τ 通用汽車	DEX-CVT
τ 通用汽車	HP-CVT P/N19355873
τ 本田	CVTF P/N 08200-9006
τ 本田	HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
τ 本田	HCF-2 P/N 08200-HCF2
τ 現代/起亞	SP-CVT 1
τ IDEMITSU	CVTF-EX1
τ 馬自達	CVTF 3320
τ 迷你庫柏	ZF CVT V1
τ 三菱	DIAMOND GREEN CVTF-J1
τ 三菱	DIAMOND GREEN CVTF-J4
τ 日產	NS-1
τ 日產	NS-2
τ 日產	NS-3
τ 寶騰	PUNCH CVT; CVTF EX-1 (SFU)
τ 雷諾	ELFMATIC
τ SATURN	P/N 22688912
τ SHELL	GREEN 1V
τ 斯巴魯	LINEARTRONIC CVTF
τ 斯巴魯	LINEARTRONIC CVTF-II; P/N K0425Y0711
τ 斯巴魯	LINEARTRONIC CV-30 P/N K0425Y0710
τ 斯巴魯	e-CVTF
τ 斯巴魯	i-CVTF
τ 斯巴魯	HIGH TORQUE P/N K0421Y0700

“Your Reliable Lubrication Choice”



## 规格

---

τ 鈴木	CVT FLUID GREEN 1
τ 鈴木	CVT FLUID GREEN 2
τ 鈴木	CVTF 3320
τ 鈴木	NS-2
τ 豐田/雷克薩斯	FE
τ 豐田/雷克薩斯	TC

19/05/2025  
5800G3LONS3REV3

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warranty only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.