油耐特 E-CVT LV

无段变速箱油 - 低粘度

商品说明

油耐特 E-CVT LV 全合成无级变速箱油由高性能全合成基础油和精心挑选的添加剂混合而成，包括摩擦改进剂、清洁分散剂、氧化抑制剂、粘度指数改进剂、腐蚀抑制剂和消泡剂。

油耐特 E-CVT LV 专为最新一代无级变速器 (CVT) 设计的自动变速器均衡油，该变速器通过钢制牵引链或皮带传输牵引力。与普通自动变速器相比，它提供了出色的动力传输比和更好的燃油经济性，许多汽车制造商已在越来越多的车型中采用CVT。

特点

- 适用于各种密封圈
- 提供出色的摩擦、氧化和热稳定性
- 优异的低温流动性，减少启动磨损
- 提供优异的稳定动力

技术特性

测试内容	测定方式	单位	
比重 @ 15 °C	ASTM D 4052	kg/L	0.839
闪点（开口杯）	ASTM D 92	°C	198
倾点	ASTM D 97	°C	-45
运动粘度 @ 40°C	ASTM D 445	cSt	26.2
运动粘度 @ 100°C	ASTM D 445	cSt	6.2
粘度指数	ASTM D 2270	-	201
颜色	-	-	琥珀色

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warranty only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.

产品规格

AUDI/ VW	P/N G 052 180 (-A2)
AUDI/ VW	P/N G 052 516 A2
BMW/ MINI/ PUNCH	EZL 799
BMW/ MINI/ PUNCH	EZL 799A
BMW	P/N 83 22 0 136 376
BMW	P/N 83 22 0 429 154
CHERY	CVTF WCF-1
CHRYSLER / FCA	MOPAR CVTF+4 P/N 05191184A
DAIHATSU	AMMIX CVTF- DFE
DAIHATSU	AMMIX CVTF- DTC
DODGE/ JEEP	NS-2
FCA	CVTF+4 P/N 05191184AA
FORD	CFT23
FORD	CFT30
FORD	MERC C
FORD	WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
GM	CVTF I-GREEN2
GM	CVT P/N 19260800
GM	DEX-CVT
GM	HP-CVT P/N19355873
HONDA	CVTF P/N 08200-9006
HONDA	HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
HONDA	HCF-2 P/N 08200-HCF2
HYUNDAI / KIA	SP-CVT 1
IDEMITSU	CVTF-EX1
MAZDA	CVTF 3320
MINI COOPER	ZF CVT V1
MITSUBISHI	DIAMOND GREEN CVTF-J1
MITSUBISHI	DIAMOND GREEN CVTF-J4
NISSAN	NS-1
NISSAN	NS-2
NISSAN	NS-3
PROTON	PUNCH CVT; CVTF EX-1 (SFU)
RENAULT	ELFMATIC
SATURN	P/N 22688912
SHELL	GREEN 1V
SUBARU	LINEARTRONIC CVTF
SUBARU	LINEARTRONIC CVTF-II; P/N K0425Y0711
SUBARU	LINEARTRONIC CV-30 P/N K0425Y0710
SUBARU	e-CVTF
SUBARU	i-CVTF
SUBARU	HIGH TORQUE P/N K0421Y0700

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511
Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warranty only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.

"Your Reliable Lubrication Choice"

产品规格

SUZUKI	CVT FLUID GREEN 1
SUZUKI	CVT FLUID GREEN 2
SUZUKI	CVTF 3320
SUZUKI	NS-2
TOYOTA / LEXUS	FE
TOYOTA / LEXUS	TC

2 September 2025
6911-3-LVREV0

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511
Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warranty only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.