

## UNT ES-Q

PCMO

### Description

Gasoline engine oil formulated with selected base fluids and technologically advanced additive to deliver outstanding engine performance and protection for today's gasoline engine powered cars and trucks. It meets the performance requirement of API SQ specification with enhanced properties in the areas of piston cleanliness, wear protection, fuel efficiency and prolong engine life.

### Properties

- τ Silky smooth operation for all high-performance engines.
- τ Increases emission system durability and improves fuel efficiency.
- τ Improves piston cleanliness and sludge control.
- τ Excellent anti-wear properties and extends service life.

### Technical Characteristics

Test Description	Method	Unit				
SAE Viscosity Grade	SAE J 300	-	<b>10W30</b>	<b>10W40</b>	<b>15W40</b>	<b>20W50</b>
Density @ 15 °C	ASTM D 4052	kg/L	0.8680	0.8681	0.8710	0.8784
Flash Point	ASTM D 92	°C	218	220	224	242
Pour Point	ASTM D 97	°C	-30	-30	-27	-18
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	73.77	101.2	108.4	172
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.12	14.81	14.6	19.49
Viscosity Index	ASTM D 2270	-	141	153	139	130
TBN	ASTM D 2896	mgKOH/g	7.2	7.2	7.2	7.2

*“Your Reliable Lubrication Choice”*



## Specifications

---

τ API	SQ-RC IN SAE 10W30
τ API	SQ IN SAE 15W40 & 20W50
τ ILSAC	GF-7A IN SAE 10W30

## Suggested for the Following uses

---

τ API	SQ IN SAE 10W40
-------	-----------------

09-04-25  
51574166G2SQREVO

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of United or any third party. United assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. United warranty only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.