

## UNT UMATIC SUPERB (API SL)

MCO

### Description

Synthetic motorcycle oil operating conditions are considerably different from passenger cars, resulting in increased specification complexity in the motorcycle oil market. This product is a tailored high-performance product to meet the unique demands of 4-stroke motorcycles. It not only lubricates critical engine components, but also provides protection for the clutch assembly and gearbox.

This product is formulated with the right combination and balance of components to combat undesirable potential issues such as gear pitting, clutch slip and higher levels of engine deposits. The advanced motorcycle oil is designed to deliver exceptional control from wear, corrosion and deposit formation as well as improved oxidative and thermal stability.

It provides unsurpassed clutch performance and friction durability throughout the oil life and extended engine life with a more consistent and enjoyable overall riding experience.

### Properties

- τ Protects engine under severe operating conditions
- τ Enhances piston and engine cleanliness
- τ Retards harmful deposit formation on vital engine parts
- τ Provides clutch friction durability

### Technical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	<b>10W40</b>
Density @ 15 °C	ASTM D 4052	kg/L	0.8597
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-30
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	98.34
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.75
Viscosity Index	ASTM D 2270	-	156
TBN	ASTM D 2896	mgKOH/g	6.1

### Specifications

- τ API SL
- τ JASO MB

03-12-24

6128G23SLMBREVO