

UNT USPORT SUPERB JASO FD

MCO

Description

Premium Two-Stroke oil formulated with highly refined base oils and synthetic components and a low ash additive package to provide excellent low smoke engine performance.

This motor oil may be used premixed with gasoline or oil injection systems. It is specifically formulated for higher temperature applications such as air-cooled two cycle motorcycle engines, chain saws, weed cutters, grass mowers and small generators. This product contains special detergents that offer excellent protection against ring sticking for these applications.

Properties

- τ Protects bearings and pistons from wear and scuffing
- τ Minimizes spark plug fouling
- τ Minimizes exhaust port blockage
- τ Low-smoke engine oil for environmentally friendly performance

Technical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.8623
Flash Point	ASTM D 92	°C	140
Pour Point	ASTM D 97	°C	-27
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	48.51
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.857
Viscosity Index	ASTM D 2270	-	131
Appearance			Red

Specifications

τ API	TC
τ ISO	L-EGD
τ JASO	FD

07-12-23
5375G25TCFDREV0