

油耐特 E-MV UN 99

變速箱油

商品說明

全合成變速箱油採用精選高黏度指數合成基礎油配製而成，可滿足多種車型的需求。作為一款通用自動變速箱油，它能夠滿足各種工具設備和動力換檔的潤滑需求。它還添加了精選的摩擦改進劑，可為各種自動變速箱提供合適的摩擦特性。憑藉增強的熱穩定性和防腐蝕性能，本產品可確保變速箱順暢運作。

本產品適用於北美、歐洲和亞洲各種原廠乘用車和商用車的變速箱，包括符合Lifeguard規格的ZF變速箱和符合Allison C-4規格的動力換檔變速箱。其性能也達到了起亞、現代和三菱等原廠對SP-III型變速箱油的要求。

不建議用於CVT、DCT或福特F型變速箱。

特點

- τ 提供卓越的氧化和熱穩定性
- τ 優異的抗磨損、摩擦性能和平穩的換檔
- τ 在極低溫和嚴苛高溫工況下均具有優異的流動性
- τ 良好的黏度穩定性

技術特性

測試內容	測定方式	單位	
比重 @ 15 °C	ASTM D 4052	kg/L	0.854
閃點 (開口杯)	ASTM D 92	°C	198
傾點	ASTM D 97	°C	-45
運動黏度 @ 40°C	ASTM D 445	cSt	32.2
運動黏度 @ 100°C	ASTM D 445	cSt	7.1
黏度指數	ASTM D 2270	-	191
顏色	-	-	紅色/琥珀

“Your Reliable Lubrication Choice”



规格

τ 愛信華納	AW-1, GM 1940773
τ 愛信華納	JWS 3309
τ 愛信華納	JWS 3324
τ 艾里遜	C-4
τ 艾里遜	TES-389B
τ 艾里遜	TES-668
τ 艾里遜	TES-295
τ 艾里遜	TES-389
τ 奧迪/大眾	TL 052 162, G 052 162
τ 奧迪/大眾	TL 052 990, G 052 990
τ 奧迪/大眾	TL 055 025, G 055 025 A2
τ 奧迪/大眾	PORSCHE 000.043.204.63
τ 奧迪/大眾	PORSCHE 000.043.205.28
τ 奧迪/大眾	TL 052 162-X, G 055 005
τ 奧迪/大眾	TL 052 162-Y, G055 162
τ 奧迪/大眾	TL 052 162-Z, G 060 162
τ 奧迪/大眾	TL 052 540-B, G 052 540
τ 寶馬	83 22 2 152 426
τ 寶馬	83 22 2 305 397 (ATF 3)
τ 寶馬	83 22 0 142 516
τ 寶馬	83 22 2 289 720 (ATF3+)
τ 寶馬	83 22 0 026 922
τ 寶馬	83 22 0 397 114 (4L)
τ 寶馬	83 22 2 163 514 (1L)
τ 寶馬	83 22 9 407 807
τ 寶馬	83222413477 (ATF 7)
τ 寶馬/MINI	83 22 7 542 290
τ DAIHATSU	AMMIX D-III ATF, 08700-K9005
τ DSIH	6P805
τ FCA	MOPAR SP-IV ATF, 68171866AA
τ FCA	ATF+3
τ FCA	ATF+2
τ FCA	MOPAR AS68, 05127382AA
τ FCA	MOPAR 69RC, 05127382AA
τ FCA	MOPAR DX-VI, 68043742AA
τ FCA	MOPAR DX-VI, 68043742AB
τ FCA	MOPAR DX-VI, 68065322AA
τ FCA	CHRYSLER MS-1872
τ FCA	CHRYSLER MS-5931, 04883077
τ FCA	MOPAR 68049954AA
τ 福特	WSS-M2C924-A, XT-8-QAW
τ 福特	FORD M

“Your Reliable Lubrication Choice”



规格

τ 福特	FRN5, XT-9-QMM5
τ 福特	WSS-M2C138
τ 福特	WSS-M2C922
τ 福特	XL-12
τ 福特	WSS-M2C195-A
τ 通用汽車	AUTO TRAK II, GM 12378508 (US)
τ 通用汽車	AUTO TRAK II, GM 10953626 (CAN)
τ 通用汽車	IID
τ 通用汽車	IIE
τ 通用汽車	IIIF
τ 通用汽車	IIIG
τ 通用汽車	IIIH
τ 通用汽車	III
τ 通用汽車	T-IV, 88900925
τ 通用汽車	ATF SATURN T-IV, 22689186
τ 通用汽車	AW-1, GM 19256039 (US)
τ 通用汽車	AW-1, GM 19256040 (CAN)
τ 通用汽車	TASA
τ 通用汽車	POWER STEERING FLUID, 89021184
τ 通用汽車	POWER STEERING FLUID, 19329450
τ 通用汽車	POWER STEERING FLUID, 1052884
τ 通用汽車	9985010, 1050017
τ 通用汽車	9985010, 1052884
τ 通用汽車	9985835, 12345866
τ 通用汽車	DEX
τ 通用汽車	WS-ATF, 88863400
τ 通用汽車	WS-ATF, 88863401
τ 本田	TYPE 3.0
τ 本田	ATF-Z1
τ 本田	ATF DW-1
τ 本田	TYPE 2.0
τ 現代/起亞	SP-IV, 04500-00115
τ 現代/起亞	SP-IV RR, 00232-19052
τ 現代/起亞	NWS 9638, 04500-00180
τ 現代/起亞	NWS 9638, 00232-19016
τ 現代/起亞	RED-1, UM040CH020
τ 現代/起亞	JWS 3314
τ 現代/起亞	JWS 3317
τ 現代/起亞	SP-II
τ 現代/起亞	SP-IV M, 00232-19057
τ 現代/起亞	SP-IV M, 00232-19059
τ 現代/起亞	SP-III 00232-19012

“Your Reliable Lubrication Choice”



规格

τ 現代/起亞	SP-III 00230-11500
τ 現代/起亞	PSF-3
τ 現代/起亞	SPH-IV, 00232-19045
τ 現代/起亞	SP
τ 五十鈴	SCS, 2-90531-200-0
τ 捷豹	FLUID 8432
τ 捷豹	FLUID JDE26444
τ JATCO	NISSAN 402
τ JATCO	3100 PL085
τ MAN	339 Z-1
τ MAN	339F
τ MAN	339 L-1
τ MAN	339 L-2
τ 馬自達	FZ, 0000-FZ-113E-01
τ 馬自達	M-III
τ 馬自達	M-V
τ 梅賽德斯-奔馳	MB 236.6
τ 梅賽德斯-奔馳	MB 236.10
τ 梅賽德斯-奔馳	MB 236.1
τ 梅賽德斯-奔馳	MB 236.2
τ 梅賽德斯-奔馳	MB 236.3
τ 梅賽德斯-奔馳	MB 236.5
τ 梅賽德斯-奔馳	MB 236.7
τ 梅賽德斯-奔馳	MB 236.9
τ 梅賽德斯-奔馳	MB 236.81
τ 梅賽德斯-奔馳	MB 236.91
τ 梅賽德斯-奔馳	MB 236.11
τ 梅賽德斯-奔馳	MB 236.12, 000-043-304-01
τ 梅賽德斯-奔馳	MB 236.12, 000-043-304-01-M853
τ 梅賽德斯-奔馳	MB 236.14
τ 梅賽德斯-奔馳	GL-450
τ 三菱	SP-II
τ 三菱	SP-III
τ 三菱	DIA QUEEN ATF J2
τ 三菱	DIA QUEEN ATF J3
τ 三菱	DIA QUEEN ATF-PA
τ 三菱	PS FLUID
τ 三菱	DIAMOND SP-III
τ 三菱	ATF-MA-1
τ 日產	MATIC D, 999MP-AA100P
τ 日產	MATIC J, 999MP-MTJ00P
τ 日產	MATIC K, 999MP-MTK00P

“Your Reliable Lubrication Choice”



规格

τ 日產	MATIC S, 999MP-MTS00P
τ 日產	MATIC W, 999MP-MTW00P
τ 日產	MATIC C
τ 日產	PSF-II
τ 北美設備製造商	LOW VISCOSITY ATF
τ 北美設備製造商	HIGH VISCOSITY ATF
τ PSA	B71 2340
τ 雷諾	DP-0
τ 薩博	93165147
τ 薩博	POWER STEERING FLUID 2634, 45 30 09 800
τ 斯巴魯	ATF
τ 斯巴魯	ATF HP, K0140Y0700
τ 斯巴魯	POWER STEERING FLUID K0209A0080
τ 鈴木	3314
τ 鈴木	3317, 99000-22B00
τ 豐田	T-IV
τ 豐田	T
τ 豐田	T-I
τ 豐田	T-II
τ 豐田	T-III
τ 豐田	WS
τ 豐田	PSF TYPE EH, 008886-01
τ 沃爾沃	1161621
τ 沃爾沃	1161521
τ 沃爾沃	1161640
τ 沃爾沃	1161540
τ 沃爾沃	97340
τ 沃爾沃	31256774 (1L)
τ 沃爾沃	31256775 (4L)
τ ZF	LIFEGUARDFLUID 5
τ ZF	LIFEGUARDFLUID 6, S671 090 255
τ ZF	LIFEGUARDFLUID 6, TYK500050
τ ZF	LIFEGUARDFLUID 6+, S671 090 281
τ ZF	TE-ML 09
τ ZF	TE-ML 21L
τ ZF	TE-ML 11 (3, 4 AND 5 SPEEDS)
τ ZF	TE-ML 11 (6 SPEEDS), S671 090 255
τ ZF	TE-ML 11 (8, 9 SPEEDS), S671 090 310
τ ZF	TE-ML 11 (8, 9 SPEEDS), S671 090 311
τ ZF	TE-ML 11 (8, 9 SPEEDS), S671 090 312
τ ZF	TE-ML 11 (8, 9 SPEEDS), S671 090 313
τ ZF	TE-ML 04D

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warrants only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.

“Your Reliable Lubrication Choice”



规格

τ	ZF	TE-ML 05L
τ	ZF	TE-ML 17C
τ	ZF	TE-ML 16L
τ	ZF	TE-ML 14A
τ	ZF	TE-ML 03D

11/1/2024
6812G3ATF99REV0

ISSUED BY UNT OIL COMPANY SDN. BHD. TEL: 03-3292 7522 / 3884 2889 FAX: 03-3292 7511

Furnishing the information contained herein does not constitute a representation by UNT OIL that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of UNT OIL or any third party. UNT OIL assumes no liability for any infringement which might arise out of product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. UNT OIL warrants only that its product meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrants of MERCHANTABILITY and FITNESS.